

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number
WO 2005/006064 A1

(51) International Patent Classification⁷: **G02F 1/1333**,
G03F 9/00, H04N 13/00

John [GB/GB]; 9 Vicarage Road, Henley-on-Thames,
Oxfordshire RG9 1HF (GB).

(21) International Application Number:
PCT/GB2004/002995

(74) Agents: **MERRYWEATHER, Colln, Henry et al.**; J.A.
Kemp & Co., 14 South Square, Gray's Inn, London WC1R
5JJ (GB).

(22) International Filing Date: 9 July 2004 (09.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0316220.3 10 July 2003 (10.07.2003) GB

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(71) Applicant (*for all designated States except US*): **OCUITY
LIMITED** [GB/GB]; 77 Heyford Park, Upper Heyford,
Oxfordshire PX25 5HD (GB).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **HARROLD,
Jonathan** [GB/GB]; 8 Robins Grove, Warwick, War-
wickshire CV34 6RF (GB). **WOODGATE, Graham,**

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: ALIGNMENT OF ELEMENTS OF A DISPLAY APPARATUS



(57) Abstract: To align a display substrate comprising an array of pixels with a component substrate comprising an array of optical components, the display substrate is divided from a display motherglass formed with an array of panels each comprising an array of pixels sufficient for a single display substrate and with, in respect of each panel, a first alignment feature having a surface relief aligned with the array of pixels. The component substrate is formed with an array of optical components and a second alignment feature having a surface relief shaped to register with the first alignment feature. The display substrates are attached to the component substrate with the first and second alignment features in registration with each other. The alignment of the first alignment feature with the array of pixels may be carried out at the motherglass stage in respect of the entire motherglass. The registration of the alignment features during attachment is a straightforward mating process which does not require precision alignment apparatus. Thus the yield can be increased.

WO 2005/006064 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*